

BÜFA



Gelcoat Unit ES1

The ideal gelcoat spraying facility
for small and medium size mouldings

Gelcoat application

Gelcoat Unit ES1

Ideal machine for the application of gelcoat, topcoat, barriercoat and even resins
Gelcoat application directly out of the drum: for smaller to medium components 1 - 3 m² in size



Description

- Easy handle of the machine.
- Proved Century gun technology.
- Soft, low emission spray fan for best gelcoat air release.
- External mixing by means of special injectors: excellent mixing of peroxide (the resin and peroxide are mixed outside).
- Low maintenance.
- Dosing of catalyst continuously visible.
- Innovative pump technology.
- Does not require cleaning due to the external mixing.
- Individual configuration of the machine is possible.

Specifications

Discharge performance, water	max. 1.6 l/min.
Volume per cycle	27 ml
Pressure ratio	32:1
Air pressure max.	6 bar
Air consumption	130-200 l/min.
Length of hoses	7.5 m
Peroxide tank	10 l

BUFAtec Spain

Polígono Industrial Sud-Est
Paseo Sanllehy, s/n. Nave 40
08213 Polinyà
Barcelona (Spain)
Phone +34 93 714 94 10
bufatec@bufatec.es
www.bufatec.es

A member of the BÜFA Group

The information given above is based on our current state of knowledge and experience. In view of the many factors that may influence working conditions and the application of our products, the user is not relieved from carrying out his own tests and experiments. Not legally binding warranty of certain properties or suitability for a particular purpose can be derived from this information. It is the responsibility of the receiver or user of our.

You'll find further information at our web page.