

BÜFA



BPU Gamma4 and Theta11

Practical user friendly and effective

Bonding paste application

BÜFAtec Bonding paste units

The Bonding paste units Gamma4 and Theta11 have achieved the best results when working with bonding pastes for high strength as well as structural bonding applications



Specifications Gamma4

Capacity per cycle	78 ml
Pressure ratio	25:1
Air pressure	6 bar
Air consumption	250 - 400 l/min.
Length of hose	7.5 m
Dimensions (L/W/H)	1000 x 1000 x 1600 mm
Weight approx.	190 kg

The BÜFAtec Bonding paste unit Gamma4 has been specially developed for working with bonding paste directly out of small pails of 25 kg. Ideal for an output of up to 50 kg per day.

BÜFAtec Spain

Polígono Industrial Sud-Est
Paseo Sanllehy, s/n. Nave 40
08213 Polinyà
Barcelona (Spain)
Phone +34 93 714 94 10
bufatec@bufatec.es
www.bufatec.es

A member of the BÜFA Group

Specifications Theta11

Capacity per cycle	521 ml
Pressure ratio	32:1
Air pressure	6 bar
Air consumption	1000-1200 l/min.
Length of hose	7.5 m
Dimensions (L/W/H)	2100 x 700 x 1600/2580 mm
Weight approx.	350 kg

The BÜFAtec Bonding paste unit Theta11 is a robust machine recommended for large adhesive applications. The large pump unit guarantees a high performance with a low maintenance.

The information given above is based on our current state of knowledge and experience. In view of the many factors that may influence working conditions and the application of our products, the user is not relieved from carrying out his own tests and experiments. Not legally binding warranty of certain properties or suitability for a particular purpose can be derived from this information. It is the responsibility of the receiver or user of our.

You'll find further information at our web page.