

BÜFA



Gelcoat spraying unit GSU 6-C/GSU 12-C

Gelcoat spraying for medium
to large sized mouldings

Gelcoat application

Gelcoat spraying unit GSU 6-C/GSU 12-C

Ideal machine for the application of gelcoat, topcoat, barriercoat and even resins
Recommended for medium to large sized parts up to 3 m²



Facts and features

- Easy handle of the machine.
- Proved, robust Century gun technology.
- External mixing technology with a soft and low emission spray jet improving deairing of gelcoat.
- Reduction of styrene emissions.
- Excellent mixing of peroxide due to the EXACT injection system.
- Low and easy maintenance.
- Innovative main pump technology.
- Does not require cleaning due to the external mixing system.
- Individual customer configurations also available.

Technical specifications

	GSU 6-C	GSU 12-C
Discharge performance, water	max. 3,3 l/mín.	max. 6 l/mín.
Volume per cycle	50 ml	100 ml
Pressure transmission ratio	32:1	15:1
Air pressure max.	6 bar	6 bar
Air consumption approx.	200-300 l/min.	200-300 l/min.
Length of hoses	7,5 m	7,5 m
Peroxide tank	10 l	10 l

BUFAtec Spain

Polígono Industrial Sud-Est
Paseo Sanllehy, s/n. Nave 40
08213 Polinyà
Barcelona (Spain)
Phone +34 93 714 94 10
bufatec@bufatec.es
www.bufatec.es

A member of the BÜFA Group

The information given above is based on our current state of knowledge and experience. In view of the many factors that may influence working conditions and the application of our products, the user is not relieved from carrying out his own tests and experiments. Not legally binding warranty of certain properties or suitability for a particular purpose can be derived from this information. It is the responsibility of the receiver or user of our.

You'll find further information at our web page.